



# The next generation 6 tube coin changer and recycler



- ✓ Proven Reliability
- ✓ Best in Class Coin Management
- ✓ Maximize Profits

World leader in payout speed and protection

coin changer



Vending



Crane Payment Solutions  
3330 Dixie Narco Blvd., · Williston, SC 29853 · USA

## The next generation 6 tube coin changer and recycler



*Intuitive menu structure and large backlit LCD for ease of programming.*



*Payout module offers 3 independent & parallel working motors. Pays out up to 6 coins per second. Built-in redundancy in case one motor fails, 4 tubes are still available.*



*Henri programming module, Operators can download new programs.*



*Robust 6-tube design. Accepts from 5 cent up to \$2 Canadian with 1742 possible tube combinations.*

### Proven Reliability

- Patented sensor system taking 40 measurements of coin parameters
- Unique Payout Redundancy Protection (PRP) System eliminates down time due to dispenser jam
- Reliable operation at the most extreme environmental conditions
- Water penetration protection of internal components

### Maximize Profits

- 3 independent payout motors for 6 coin tubes -reduces down time
- 6 coin per second payout minimizes transaction times
- Huge range of payout configurations available to optimize the number of vends
- Fast configuration and updates of multiple units using HENRI setting module
- High capacity 6 tubes virtually eliminate exact change situations
- Easy and fast access to sorting area for easy cleaning
- The bright, easy to read graphics display notifies drivers of issues

### Coin Management

- Multiple float modes to optimize the amount of change in machine
- Industry's highest capacity replenishing 6 tube changer
- Multiple par options to provide the flexibility you need
- User friendly intuitive menu structure for easy individual configuration
- Suggests optimal coin tube configuration based on site use data

currenza <sup>®</sup> c <sup>2</sup> Coin Changer Specifications	
Coins Accepted	US: .01, .05, .10, .25, .50, \$1 CANADA: .05, .10, .25, \$1, \$2
Acceptance Rate	95% specification, 98% typical
Operating temperature	-25°C to +80°C / -13°F to +176°F
Number of tubes	6 replenishing
Dispense rate	2 coins per second per motor Up to 6 coins per second
Dispense motors	3
Protocol	MDB
Display	Backlit LCD
Weight	3.8 lbs